

The A Proctor Group Ltd

The Haugh

Blairgowrie

Perthshire PH10 7ER



Product: Wraptite

Conditions of acceptance;

1. The Product must be installed in strict accordance with BBA certificate 15/5274 (PS1 & PS2)
2. The BBA certificate 15/5274 (PS1 & PS2) must remain valid.
3. We will accept the use of Wraptite SA Breather Membrane for use in warm non-ventilated roofs in supported applications, provided it is installed, used and maintained in accordance with this Certificate, in relation to the Technical Manual, Chapter 11.
4. We will accept the use of Wraptite SA Breather Membrane for use in wall constructions, provided it is installed, used and maintained in accordance with this Certificate, in relation to our Technical Manual, Section 6.
5. For roofs with an insulated inclined ceiling, ventilation above or below the underlay will not be required provided that the passage of moisture by diffusion and by convection is controlled, eg by a vapour control layer or a continuous envelope of insulation with a high vapour resistance. Ventilation may be required if specified by the tile manufacturer or where the roof covering is airtight, as described in BS 5250 : 2011. (PS1 - non-ventilated warm roofs).
6. The product is self-adhered to the support, with counter battens at least 12 mm thick to create an air space between the product and the tiles for drainage and vapour dispersal (PS1 - non-ventilated warm roofs).
7. The product is designed to be installed by competent contractors experienced with this type of product
8. The product may be used over sarking boards of softwood, C4 grade chipboard or water-resistant grade OSB (PS1 – walls and floors).
9. Upper layers should overlap layers to shed water away from the sheathing. Vertical laps should be staggered wherever possible



PRODUCT ACCEPTANCE

10. Vertical and horizontal laps should not be less than 75 mm.

LABC Warranty has awarded this Certificate to the company named above for the product described herein. This product has been assessed by LABC Warranty as being fit for its intended use provided it is installed, used and maintained as set out in the Product Acceptance Document.

Date: 18/02/2021

Signed: 