

Protech GM Primer

GAS PROTECTION

DESCRIPTION

Protech GM Primer is used in conjunction with Protech SAGM in order to consolidate the substrate and ensure complete bond development.

Protech GM Primer is supplied as a single pack brush applied liquid coating.

USES

Protech GM Primer seals porous substrates and encourages the adhesion of bituminous waterproofing systems and sheet coverings. It may be applied successfully to a wide range of surfaces.

APPLICATION

It is recommended that two coats of Protech GM Primer should be applied, and that it is dry prior to installing Protech SAGM.

METHOD OF USE

Surfaces should be clean, i.e. free from all oil, grease, dirt, dust and loose debris. On metal surfaces all loose rust should be removed using a wire bristled brush and where advanced signs of corrosion are evident these areas should initially be treated with a rust inhibitor. Surfaces should preferably be dry although Protech GM Primer will adhere to damp but not wet surfaces. Application should not take place in temperatures below 5°C.



PRODUCT DATA

Colour	Black
Coverage:	6 - 8m ² / litre
Viscosity:	500cP
Specific Gravity	0.92
Solids Content	48% w/w
Flash Point	>39°C
Drying Time	Normally touch dry after 30 minutes. Completely dry after 2-6 hours



Download a full Gas Protection brochure from our website...

www.proctorgroup.com

BGA British Geomembrane Association



n55Plus



contact@proctorgroup.com | +44 (0) 1250 872261

Revised January 2021

Proctor
Group