

PROFLOOR DYNAMIC BATTENS

PROFLOOR DYNAMIC BATTENS

Product specification to be Profloor Dynamic Battens by The A Proctor Group, Blairgowrie

Manufacturer

Name A Proctor Group Ltd
 Web www.proctorgroup.com
 Email technical@proctorgroup.com
 Tel +44 (0) 1250 872261
 Fax +44 (0) 1250 872727
 Address The Haugh, Blairgowrie, Perthshire PH10 7ER

Detailed Description

Acoustic Floating Floor System to be used shall be Profloor Dynamic Battens supplied by The A Proctor Group, Blairgowrie. Profloor Dynamic Battens are timber battens with a bonded dual foam resilient layer designed to provide impact sound reduction in separating floors for both Refurbishment and New Build projects.

Product

Product performance specification as follows:

Standard Battens

Nominal height (uncompressed) 55, 67, 81 or 91mm
 Width 45mm
 Length 2.4m

Support Battens

Nominal height (uncompressed) 43, 55, 70 or 80mm
 Width 45mm
 Length 2.4m

Material

Open and closed cell resilient layer bonded to timber battens

Accessories

Flanking Strip: 5mm x 50, 75, 100, 125 or 150mm x 10m
 Profloor Adhesive: 1 litre bottles

Certification

Minimum required: The timber should be responsibly sourced, being either FSC or PEFC certified.

Technical Properties

- Resilient Layer Composition: to be dual layered comprising open and closed foams
- Timber Type: timber to be home grown
- Compression under normal loadings: Standard Battens to be no less than 8-10mm, Hi Load Battens to be no less than 1-2mm
- RD Compliance: FFT1, FFT3 & FFT80 (Scotland)
- Refurb Compliance: suitable for improving the impact sound reduction between existing separating floors
- Timber or Concrete Floor: to be suitable for use in timber and concrete floors

Profloor Dynamic Batten System is specified and detailed similar to a standard batten for the purpose of supporting the chosen floor finish, but has the advantage of providing effective isolation of the floor finish from the structure. Significant improvement in Impact and Airborne Sound Insulation can be obtained when using Profloor Dynamic Batten System in timber or concrete construction. Standard: for normal domestic loadings (up to 1.4kN/m²) Hi-load: for floors with higher loadings (up to 4.0kN/m²)

Benefits

- Significantly reduces impact and airborne noise pollution in multi - level buildings
- Designed to last the lifetime of the floor
- Supremely versatile, making it suitable for most domestic flooring applications
- Foams are resistant to biological attack
- Non-load bearing partition walls can be erected on the finished acoustic floor where a double batten run has been positioned below

Product Reference [Profloor Dynamic Battens](#)

Revision Date: 28.05.2018