

PROFLOOR SOLO DECK 23

PROFLOOR SOLO DECK 23

Product specification to be Profloor Solo Deck 23 by The A Proctor Group, Blairgowrie

Manufacturer

Name A Proctor Group Ltd
 Web www.proctorgroup.com
 Email technical@proctorgroup.com
 Tel +44 (0) 1250 872261
 Fax +44 (0) 1250 872727
 Address The Haugh, Blairgowrie, Perthshire PH10 7ER

Detailed Description

Acoustic Floating Floor System to be used shall be Profloor Solo Deck 23 supplied by The A Proctor Group, Blairgowrie. Profloor Solo Deck 23 is a 18mm T&G chipboard and composite foam laminate. It is used to provide impact sound reduction in separating floors for both Refurbishment and New Build projects.

Product

Product performance specification as follows:

Standard Deck

23mm x 600mm x 2400mm

Material

Open and closed cell composite foam bonded to 18mm P5 grade chipboard

Accessories

Flanking Strip: 5mm x 125mm x 10m (available with or without double sided tape)

Profloor Adhesive: 1 litre bottles

Certification

Minimum required: The timber in should be responsibly sourced, being either FSC or PEFC certified.

Technical Properties

- Resilient Layer Composition: to be 5mm recycled composite foam
- Chipboard: to be 18mm P5 grade T&G
- Compression under normal loadings: Standard Deck to be no more than 1-2mm
- RD Compliance: FFT5
- Refurb Compliance: suitable for improving the impact sound reduction between existing separating floors
- Timber or Concrete Floor: to be suitable for use in timber and concrete floors

Profloor Solo Deck 23 is a shallow profile overlay board comprising a 5mm resilient layer bonded to flooring grade, tongue and groove chipboard. This, combined with a minimal impact on floor to ceiling height, makes Profloor Solo Deck 23 ideally suited to refurbishment, conversion or new build projects, and is an economical floating floor solution.

Benefits

- Robust Detail-compliant FFT5
- Intended for use with concrete subfloors
- Certified for use with relevant RD Floor constructions
- Recycled composite resilient layer
- One type satisfies requirements of both standard and hi-load areas (domestic applications)
- Suitable for new build and refurbishment
- FSC certified

Product Reference [Profloor Solo Deck 23](#)

Revised Date: 28.05.2018